

1.0 GENERAL DESCRIPTION

- 1.1 The unit shall be vandal resistant, a speaker with location identification, model A400 from Emcom Systems, no substitutions. The unit shall use a blue light and a speaker. It shall fit Emcom's IP60XX series of VoIP phones.

2.0 CONSTRUCTION

- 2.1 The unit shall measure 10.0" H x 7.0" W x 4.13" D.
- 2.2 The unit shall measure 6 lbs.
- 2.3 The housing shall be constructed of 16 gauge stainless steel (thickness .062") with No. 4 brushed finish.
- 2.4 The beacon shall be constructed of blue polycarbonate material in blue.

3.0 MOUNTING

- 3.1 The unit is typically mounted in conjunction with any Emcom IP60XX phone that has a built-in Speaker/Beacon driver PC Board.
- 3.2 The unit shall have four .40" diameter mounting holes on the back.
- 3.3 The unit can be mounted to any surface or it can be used with an Emcom A401 Pole Mounting Kit.

4.0 FEATURES

- 4.1 Connections are one audio pair and one beacon pair.
- 4.2 Operational temperature shall be -30° to +55° Celsius (-22°F to +131° Fahrenheit).
- 4.3 The front panel shall be removed for installation purposes via four vandal-resistant screws.

5.0 POWER

- 5.1 The submersible speaker shall use 4 Ohms, 15 Watts 120-8,000 HZ with an output of 95Db @ 1 Watt/Meter.
- 5.2 The unit shall have a 360 degree blue beacon and visible from 4000 feet. The beacon's current source is 350Ma.

6.0 WARRANTY

6.1 The A400 shall be warrantied against any defects in material and workmanship, under normal use and proper installation, for a period of 2 years from the date of shipment by the manufacturer. If the unit is found by the manufacturer to be defective within the warranty period, the manufacturer shall repair and/or replace any defective parts, provided the equipment is returned to the manufacturer.

7.0 MANUFACTURER

7.1 The Manufacturer shall be Emcom Systems. 609-585-5500, 127 Route 206 South, Suite 27, Trenton, New Jersey 08610. www.emcomsys.com. THERE ARE NO EQUIVALENTS.