



H303 Surface Mount Box With 45° Pitched Roof and Drip Cap

Architectural & Engineering Specifications

1.0 GENERAL DESCRIPTION

- 1.1 The unit shall be a vandal-resistant, wall mount stainless steel enclosure with 45° degree roof, integrated drip cap, model H303 from Emcom Systems, no substitutions. It shall accommodate Emcom's IP60XX series of VoIP phones.

2.0 CONSTRUCTION

- 2.1 The enclosure shall be constructed of 16 gauge stainless steel (thickness .062") with No. 4 brushed finish.
- 2.2 The unit shall measure 18.50" high, 11" wide, 5.25" deep.
- 2.3 The unit shall weigh approximately 8 lbs.
- 2.4 Emcom VoIP phones shall mount to the unit via 10-32 stainless steel panel nut retainers. The retainers shall be replaceable.

3.0 MOUNTING

- 3.1 The unit shall have four .40" diameter mounting holes on the back and shall be compatible with model A401 Pole Mounting Kit from Emcom.

4.0 FEATURES

- 4.1 The unit shall contain an integrated 45° degree pitched roof to remove any potentially harmful corners.
- 4.2 The unit shall have an integrated drip cap to direct water and liquids away from the VoIP phones.
- 4.3 Signage shall be a highly visible, durable label with a gray reflective background with contrasting, bold text or symbols.
- 4.3.1 Custom text, symbols, and colors are available.
- 4.4 The unit shall accept the model H305 Door from Emcom.



H303 Surface Mount Box With 45° Pitched Roof and Drip Cap

Architectural & Engineering Specifications

5.0 COMPLIANCE

5.1 When properly installed, the unit shall meet NEMA 4X.

6.0 OPTIONS

6.1 The H303 shall be available in powder coating of either safety yellow or red.

7.0 WARRANTY

7.1 The H303 shall be warranted against any defects in material and workmanship, under normal use, for a period of 2 years from the date of shipment by the manufacturer. If the unit is found to be defective within the warranty period, the manufacturer shall repair and/or replace any defective parts, provided the equipment is returned to the manufacturer.

8.0 MANUFACTURER

8.1 The Manufacturer shall be Emcom Systems. 609-585-5500, 127 Route 206 South, Suite 27, Trenton, New Jersey 08610. www.emcomsys.com. THERE ARE NO EQUIVALENTS.