

### **1.0 GENERAL DESCRIPTION**

- 1.1 The unit shall be a high impact vandal-resistant, fully sealed thermoplastic enclosure, model H340 from Emcom Systems. It shall accommodate the Emcom IP60XX series of VoIP phones.

### **2.0 CONSTRUCTION**

- 2.1 The housing shall be constructed of high-impact 1/4" thick Kydex ®.
- 2.2 The unit shall measure 13.13" high, 9.75" wide, 4.0" deep.
- 2.3 The unit shall weigh approximately 3 lbs.
- 2.4 Emcom IP60XX VoIP phones shall mount to the unit via 10-32 screws.

### **3.0 MOUNTING**

- 3.1 The unit shall have four .40" diameter mounting holes on the back and shall be compatible with model 401 Pole Mounting Kit from Emcom.
- 3.2 Four 2" diameter fender washers shall be provided to secure unit to the surface.
- 3.3 Four 2" diameter fender washers shall be provided to be used as shims for mounting unit to an uneven surface.

### **4.0 FEATURES**

- 4.1 Standard color is pewter gray. Custom colors are available.
- 4.2 Custom labels are available to apply to the sides and door of the enclosure.

### **5.0 COMPLIANCE**

- 5.1 When properly installed, the unit shall meet NEMA 4X.
- 5.2 When properly installed, the unit shall meet ADA requirements for Wall Protrusion (4").
- 5.3 The enclosure shall meet UL94V-0 for Plastic Flammability Standards.

# H340 Rugged Phone Enclosure

## Architectural & Engineering Specifications

### **6.0 WARRANTY**

6.1 The H340 shall be warrantied against any defects in material and workmanship, under normal use and proper installation, for a period of 2 years from the date of shipment by the manufacturer. If the unit is found to be defective within the warranty period, the manufacturer shall repair and/or replace any defective parts, provided the equipment is returned to the manufacturer.

### **7.0 MANUFACTURER**

7.1 The Manufacturer shall be Emcom Systems. 609-585-5500, 127 Route 206 South, Suite 27, Trenton, New Jersey 08610. [www.emcomsys.com](http://www.emcomsys.com). THERE ARE NO EQUIVALENTS.