



IP6002 Modular VoIP Phone Board with Rugged Housing

Architectural & Engineering Specifications

1.0 GENERAL DESCRIPTION

- 1.1 The unit shall be high quality, DSP-based full duplex VoIP phone board contained in a rugged aluminum housing, model IP6002 from Emcom Systems, no substitutions.

2.0 CONSTRUCTION

- 2.1 The unit shall measure 5.75" high x 4.75" wide x 1.70" deep
- 2.2 The housing shall be 14 gauge aluminum with one side open for board connections.
- 2.3 The unit shall weigh 2 lbs.

3.0 MOUNTING

- 3.1 The phone shall be mounted with the two installed DIN rail clips. The housing provides three different locations to mount the DIN rail clips for a wide variety of mounting options.

4.0 FEATURES

- 4.1 The phone shall have connection points for a speaker, microphone, two call indicator lights, and call activation switch.
- 4.2 The digital signal processor shall include background noise reduction.
- 4.3 The phone shall have the ability to be programmed remotely including volume adjustments thru a web browser.
- 4.4 The phone shall be fully compliant with Emcom's EmVista Maintenance Software.
- 4.5 The phone shall be a low profile design for mounting behind elevator operating panels.
- 4.6 The phone shall be compatible with two elevator panel adaptors. The Emcom IP6002-2 panel adaptor is designed to fit into Janus/VPP phone applications. The Emcom IP6002-3 panel adaptor is designed to fit into Control phone applications.

5.0 POWER

- 5.1 The phone shall be capable of being powered from 12-48 VDC Power or VIA POE per IEEE 802.3af.
- 5.2 Non-volatile memory shall ensure that programming is retained during power loss.

6.0 CONNECTORS

- 6.1 The phone shall have 2 RJ-45 ports and 1 power connector.



IP6002 Modular VoIP Phone Board with Rugged Housing

Architectural & Engineering Specifications

6.2 The phone shall contain two auxiliary contacts that are Opto-isolated and rated 120mA - 250VAC.

7.0 COMPLIANCE

7.1 The phone shall be UL 60950-1 and CSA C22.2 No.609050-1 Listed.

8.0 WARRANTY

8.1 The IP6002 shall be warrantied against any defects in material and workmanship, under normal use and proper installation, for a period of 2 years from the date of shipment by the manufacturer. If the unit is found to be defective within the warranty period, the manufacturer shall repair and/or replace any defective parts, provided the equipment is returned to the manufacturer.

9.0 MANUFACTURER

9.1 The Manufacturer shall be Emcom Systems. 609-585-5500, 127 Route 206 South, Suite 27, Trenton, New Jersey 08610. www.emcomsys.com. THERE ARE NO EQUIVALENTS.