

### **1.0 GENERAL DESCRIPTION**

- 1.1 The unit shall be a vandal-resistant, extended wall mount enclosure and constructed of stainless steel, model H305 from Emcom Systems, no substitutions. It shall fit Emcom's IP60XX series of VoIP phones.

### **2.0 CONSTRUCTION**

- 2.1 The housing shall be constructed of 16 gauge stainless steel (thickness .062") with No. 4 brushed finish.
- 2.2 The unit shall measure 12.3" high, 10" wide, 3.5" deep.
- 2.3 The unit shall weigh approximately 6 lbs.
- 2.4 There shall be two gaskets; one for sealing the door to the frame and one for sealing the frame to the IP60XX series VoIP phone.

### **3.0 MOUNTING**

- 3.1 Six #10 mounting holes shall be provided for mounting the unit to Emcom model H300.

### **4.0 FEATURES**

- 4.1 Door shall have a water-tight keyed cam lock on the side for optional access control.
- 4.2 Door shall be self-closing when opened less than 100 degrees. Door shall have a mechanism to hold ajar when opened beyond 120 degrees.
- 4.3 The unit shall be compatible with model H300 wall mount.

### **5.0 OPTIONS**

- 5.1 The H305 shall be available in powder coating of either safety yellow or red.

### **6.0 WARRANTY**

- 6.1 The H305 shall be warrantied against any defects in material and workmanship, under normal use and proper installation, for a period of 2 years from the date of shipment by the manufacturer. If the unit is found by the manufacturer to be defective within the warranty period, the manufacturer shall repair and/or replace any defective parts, provided the equipment is returned to the manufacturer.



# H305 Door for H300 Enclosure

Architectural & Engineering Specifications

## **7.0 MANUFACTURER**

- 7.1 The Manufacturer shall be Emcom Systems. 609-585-5500, 92 N. Main Street, Building 18A, Windsor, New Jersey 08561. [www.emcomsys.com](http://www.emcomsys.com). THERE ARE NO EQUIVALENTS.