



IP6500-2 Rugged, Full Duplex, VoIP, Hands-Free Phone with DSL Option


The IP6500-2 is an ADA compliant, hardened, vandal-resistant, full-duplex, intelligent hands-free emergency assistance phone that provides VoIP (Voice over Internet Protocol) communications utilizing SIP (Session Initiation Protocol). The rugged enameled steel front panel with sealed speaker, microphone and activation button ensures long product life and provides assurance that vital calls will get through under the harshest of conditions. The IP6500-2 may be used in a direct Ethernet connection for distances below 328 feet (100 meters) or it may be connected at distances up to 1500 feet (457 meters) using the built-in DSL interface. The IP6500-2 is programmed via a web browser or is remotely supervised, tested and programmed using an Emcom Systems' EmVista Maintenance Station.

Advantages

- Full Duplex
- Built In DSL Interface
- Wide Operating Temp. Range
- 1" Metal "HELP" Button
- Distances up to 1500 Feet
- 2 Visual Call Indications
- Metal Braille Plate
- Background Noise Reduction Using DSP
- Remote Programming and Volume Adjust Via Web Browser or EmVista Maintenance Station
- 3 Port IP Switch for Daisy Chaining
- 2 Year Warranty



Dimensions



Specifications

Dimensions:	4.9" W x 9.0" H x 2.0" D
Panel:	18 Ga (.048" Thk.) Enameled Steel
Weight:	3 lbs.
Connectors:	2 RJ-45, 1 RJ-11, 2 Aux. Contacts 1 Power
Operating Temp:	-30° C to +55° C (-22°F to +131°F)
Power:	24 – 48 VDC 8 Watts at Full Volume
2 Aux. Contacts:	120mA - 250VAC Rating, Opto-isolated
Freq. Response:	300Hz - 3400Hz
MTBF:	Greater than 90,000 Hours
Compatibility:	Mitel Cisco Genetec

PO Box 59
Windsor, NJ 08561

92 N Main St , Bldg. 18A
Windsor, NJ 08561

Contact: info@emcomsys.com
+1 (609) 585-5500
www.emcomsys.com