



T1250 Series Phones

The T1250 is ideal for installation in elevators, for areas of rescue or any indoor area requiring emergency telephones. It can be connected to analog telephone lines from any CO, PBX or Key systems, or integrated into VOIP systems through a VOIP gateway.



Part #: T1250B
Dimensions: 8.5" H x 4.8" W x 2.6" D
Weight: 3 lbs.
Material: Black enamel cold-rolled steel



Part #: T1250S
Dimensions: 9" H x 6" W x 1.75" D
Weight: 3.5 lbs.
Material: 13 ga (0.090") brushed stainless steel



Part #: T1250E
Dimensions: 6" H x 5" W x 2.25" D
Weight: 1.5 lbs.
Material: 0.125" ABS plastic

Key Features:

- Surface mount
- True Talk™ Full Duplex Speaker Phone
- Complies with the requirements of the Americans with Disability Act (ADA)
- FCC registered
- Built in four number dialer
- Two visual call progress indicators
- Automatic number identifier
- Tone feature for patron signaling
- One programmable auxiliary output
- Remotely programmable
- One or two programmable messages
- Programmable ring count
- Phone line monitoring available

Specifications:

- Power: 12-24V isolated DC, or powered from 110VAC converter provided
- Talk Battery: 24-56VDC
- Current Range: 11-120mA
- REN: 1.1
- Dialing: Tone or pulse
- Frequency Response: 300-3,000Hz
- Operating Temperature: 23° to 122° F (-5° to 50° C)
- Regulatory Standards
- FCC Reg No: 5CDUSA-30708-AL-E
- Industry Canada No: 26817738A