



T2100

Description:

The T2100f emergency telephone are designed to withstand the rigors of harsh weather and environments, with electronics sealed with a Mil-Spec protective coating and protected speaker and microphone openings. They can be connected to analog telephone lines from any CO, PBX or Key systems, or integrated into VOIP systems through a VOIP gateway.



T2100

Key Features:

- Flush mount
- True Talk™ Full Duplex Speaker Phone
- FCC registered
- Built in four number dialer
- Two visual call progress indicators
- Automatic number identifier
- Tone feature for patron signaling
- Two programmable auxiliary outputs
- Remotely programmable
- One or two programmable messages
- Programmable ring count
- Phone line monitoring available

Specifications:

- Dimensions: 11.75" H x 8.5" W x 2.7" D
- Weight: 6 lbs.
- Material: 12 ga (0.012") brushed stainless steel
- Power: 12-24V isolated DC, or powered from 110VAC converter provided
- Talk Battery: 24-56VDC
- Current Range: 11-120mA
- REN: 1.1
- Dialing: Tone or pulse
- Frequency Response: 300-3,000Hz
- Operating Temperature: -4° to 140° F (-20° to 60° C), 23° to 122° F (-5° to 50° C) (T2100C only)
- Regulatory Standards
- FCC Reg No: 5CDUSA-30708-AL-E
- Industry Canada No: 26817738A